



CXP 808HD

Business VoIP Phone



Smart Features

- ✓ HD Voice
- ✓ Opus Codec
- ✓ 2 x Gigabit Ethernet port
- ✓ 1x USB port
- ✓ Stand with 3 adjustable angles
- ✓ 2.4GHz Wi-Fi
- ✓ Wall mountable
- ✓ Phone book (2000 records)
- ✓ Call history: In/Out/missed (60 records)
- ✓ Voice mail, call park, call pickup
- ✓ 4 Soft Keys & 4 Line keys
- ✓ 5 Navigate Keys
- ✓ Volume+/-
- ✓ BLF & Message waiting indicator (MWI)
- ✓ 7 features keys: message, headset, hold, mute transfer, redial, hands-free speakerphone
- ✓ 1 x RJ9 Headset port
- ✓ 1 x Power adapter
- ✓ PoE (IEEE 802.3af) Class-2

Overview

Mid-level VoIP Phone, ideal for professionals and managers with moderate call load. CXP-808 HD is a 8-Line SIP phone with 3.5-inch IPS colour screen. It features dual Gigabit Ethernet ports, USB 2.0 port and RJ9 port, Integrated PoE and 2.4G Wi-Fi to help business maximize the use of wireless network, reduce internet cable cost and support clean and uncluttered workspace communications. CXP-808HD delivers distraction-free communications with industry leading Smart Noise Filtering Technology with excellent sound quality without extraneous noises and allows fluent conversations..

SIP Account

- 8 SIP Account

Conference

- 6 Way

Phone Feature

- Call hold, mute, DND, redial, auto answer
- One-touch speed dial, hotline, SIP message
- Call forward, call waiting
- call transfer (attended/blind)
- Paging, intercom
- Direct IP call without SIP proxy, Dial rule

Wi-Fi

- 2.4GHz Wi-Fi

Wideband Codec

- G.722, Opus, AMR-WB(Optional), G.711WB(Optional)

Narrowband Codec

- G.711(A/u), iLBC, G.729AB, G.723, G.726, AMR-NB(Optional)

DTMF

- In-band, RFC 2833 and SIP info

Phone book

- 2000 records, Black list
- XML/LDAP remote phonebook
- Phonebook search/import/export
- Call history: dialed/received/missed (60 records)

IP-PBX Features

- BLF, Anonymous call, anonymous call rejection
- Voice mail, call park, call pickup
- Message waiting indicator (MWI)

Soft Keys

- 4

Navigate Keys

- 5

Volume+/-

- YES

Display

- 3.5" 480x320-Pixel Color Display

Ethernet (RJ45)

- 2x 10/100/1000 Base-T
- Support PoE (IEEE 802.3af), class 2

Headset

- 1x RJ9

Handset

- 1x RJ9

USB

- 1x USB

Management

- Configuration: browser/phone/auto-provision
- TFTP/HTTP/HTTPS for Auto Provisioning
- TR069 (TR104/TR106) , Reset to factory
- reboot , system, log
- DNS/DNS SRV (RFC 1706, RFC 2782)
- NAPTR for SIP URI lookup (RFC 2915)
- DHCP server and DHCP client

Power

- PoE (IEEE 802.3af), Class-2
- AC/DC Adapter : 5V, 1A (Optional)

Power consumption (PSU)

- 1.5-3.5W

Power consumption (PoE)

- 1.9-4.5W

Operation temperature

- 0~45°C

Relative humidity

- 10%~90% (No Condensing)

Storage temperature

- 25~ 65°C

Line Key

- 8 Line keys

BLF/DSS Key

- Up to 21 DSS/BLF keys

Features keys

- 7

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT Traversal By STUN
- Proxy mode and peer-to-peer SIP link mode
- Static IP and DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- SDP (RFC 2327), UDP/TCP
- Mutil-VLAN, DSCP and 802.1p QoS
- SRTP > TLS >, HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication , IEEE802.1X
- Open VPN, IPv4 /IPv6, Dualstack IPv4/IPv6
- RTP/RTCP (RFC 1889, RFC 1890)
- ARP/RARP (RFC 826/903)
- IEEE802.1Q VLAN/802.1p/DSCP
- SNMPv2 , LLDP/CDP/DHCP VLAN
- Compliance**
- Compliance: CE, FCC, UL, RoHS
- EMC: 47 CFR FCC Part 15: 2015 Subpart-B (Class-A)

Creative is a Leading state of the art technology based VoIP & Unified Communication System Developer and Provider and focused on research & Innovation , Creative offers global standard Embedded SIP-PBX , VoIP Gateway, IP-Phones and Telephony application software to cater SoHO, SME, SMB and Enterprise Communication requirements..

Email: info@creativetele.in

Phone: +91-54123-56941

Web: www.creativetele.in

Creative Communication