



CXP 810HD

Business VoIP Phone



Smart Features

- ✓ 4.3" 480 x 272px Colour IPS Touch Screen
- ✓ 10 SIP accounts
- ✓ Up to 64 DSS/BLF keys
- ✓ HD Voice
- ✓ Opus Codec
- ✓ 2 x RJ45 (10/100/100 Base-T Ethernet Port)
- ✓ Stand with 3 adjustable angles
- ✓ 2.4GHz Wi-Fi inbuilt
- ✓ 5GHz Wi-Fi using Wi-Fi dongle
- ✓ Wall mountable
- ✓ Phone book (2000 records)
- ✓ XML/LDAP remote phonebook
- ✓ Call history: In/Out/missed (60 records)
- ✓ BLF & Message waiting indicator (MWI)
- ✓ Voice mail, call park, call pickup
- ✓ 10 Line keys (touchable)
- ✓ 4 soft keys (touchable)
- ✓ 6 Way Conference
- ✓ PoE (IEEE 802.3af) Class-3

Overview

CXP810HD is the most powerful High-End IP Phone with 4.3" Touch Screen Color LCD display, designed for the high-call volume user who requires a suite of call control and efficiency focused features. Bring heavy communications under control by utilizing the CXP810HD's high-line access, BLF/speed-dial support and other control focused features. The phone supports up to 10 SIP accounts, 2.4GHz Wi-Fi connection and dual-port Gigabit Ethernet. With PoE, BLF and programming features, FIP15G offers productivity features for speed of operations and collaboration. Thus, making it an ideal choice for reliable and flawless communication.

SIP Account

- 10 SIP Account

Conference

- 6 Way

Phone Feature

- Call hold, mute, DND, redial, auto answer
- One-touch speed dial, hotline, SIP message
- Call forward, call waiting
- call transfer (attended/blind)
- Paging, intercom
- Direct IP call without SIP proxy, Dial rule

Wi-Fi

- 2.4GHz Wi-Fi

Wideband Codec

- G.722, Opus, AMR-WB(Optional), G.711WB(Optional)

Narrowband Codec

- G.711(A/u), iLBC, G.729AB, G.723, G.726, AMR-NB(Optional)

DTMF

- In-band, RFC 2833 and SIP info

Phone book

- 2000 records, Black list
- XML/LDAP remote phonebook
- Phonebook search/import/export
- Call history: dialed/received/missed (60 records)

IP-PBX Features

- BLF, Anonymous call, anonymous call rejection
- Voice mail, call park, call pickup
- Message waiting indicator (MWI)

Soft Keys

- 4 Soft keys (Touchable)

Navigate Keys

- N/A

Volume+/-

- YES

Display

- 4.3" 480 x 272px Color IPS Touch Screen

Ethernet (RJ45)

- 2x 10/100/1000 Base-T
- Support PoE (IEEE 802.3af), class 3

Headset

- 1x RJ9

Handset

- 1x RJ9

USB

- 1x USB

Management

- Configuration: browser/phone/auto-provision
- TFTP/HTTP/HTTPS for Auto Provisioning
- TR069 (TR104/TR106), Reset to factory
- Reboot , System, Log
- DNS/DNS SRV (RFC 1706, RFC 2782)
- NAPTR for SIP URI lookup (RFC 2915)
- DHCP Server and DHCP Client

Power

- PoE (IEEE 802.3af), Class-2
- AC/DC Adapter : 5V, 1A (Optional)

Power consumption (PSU)

- 1.5-3.5W

Power consumption (PoE)

- 1.9-4.5W

Operation temperature

- 0~45°C

Relative humidity

- 10%~90% (No Condensing)

Storage temperature

- 25~ 65°C

Line Key

- 10 Line keys (Touchable)

BLF/DSS Key

- Up to 64 DSS/BLF keys (Touchable)

Features keys

- 3 (Headset, Mute and Hands-Free)

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT Traversal By STUN
- Proxy mode and peer-to-peer SIP link mode
- Static IP and DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- SDP (RFC 2327), UDP/TCP
- Mutil-VLAN, DSCP and 802.1p QoS
- SRTP > TLS >, HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication , IEEE802.1X
- Open VPN, IPv4 /IPv6, Dualstack IPv4/IPv6
- RTP/RTCP (RFC 1889, RFC 1890)
- ARP/RARP (RFC 826/903)
- IEEE802.1Q VLAN/802.1p/DSCP
- SNMPv2 , LLDP/CDP/DHCP VLAN
- Compliance**
- Compliance: CE, FCC, UL, RoHS
- EMC: 47 CFR FCC Part 15: 2015 Subpart-B (Class-A)

Creative is a Leading state of the art technology based VoIP & Unified Communication System Developer and Provider and focused on research & Innovation , Creative offers global standard Embedded SIP-PBX , VoIP Gateway, IP-Phones and Telephony application software to cater SoHO, SME, SMB and Enterprise Communication requirements..

Creative Communication

Email: info@creativetele.in

Phone: +91-54123-56941

Web: www.creativetele.in